

IN-PLACE FULL DEPTH RECLAMATION OF BITUMINOUS PAVEMENT AND UNDERLYING GRANULAR - Item No.

Special Provision No. 330S01

May 2010

Amendment to OPSS 330, May 1994**330.07 CONSTRUCTION****330.07.02 Reclamation of Bituminous Pavement and Underlying Granular**

Subsection 330.07.02 of OPSS 330 is deleted in its entirety and replacing it with the following:

The bituminous pavement and underlying granular shall be reclaimed to the widths specified in the contract.

The processed depth shall be such that the blended material shall contain a maximum of 50% by mass of asphalt coated aggregate in the final blend as determined by MTO Lab. Test No. LS 621.

The operation of full depth reclamation shall ensure that all of the mixed material passes the 26.5 mm sieve and not more than 75% passes the 4.75 mm sieve.

330.07.03 Surface Shaping and Compacting

Subsection 330.07.03 of OPSS 330 is amended by deleting the first sentence in its entirety and replacing it with the following:

The graded surface of the processed material including existing shoulders shall conform to the requirements of OPSS 301.

Subsection 330.07.03 of OPSS 330 is amended by the addition of the following:

Surfaces of processed material which have been exposed to traffic that are to receive granular base material to depths of up to 100 mm as required in the contract shall be scarified immediately prior to placement of the base course material.

330.07.04 Operational Constraint

Subsection 330.07.04 of OPSS 330 is amended by the addition of the following:

The existing shoulders shall also be shaped and compacted to final grade prior to closing down operations each day.

330.08 QUALITY ASSURANCE**330.08.01 Samples for Testing**

Subsection 330.08.01 of OPSS 330 is deleted in its entirety and replaced by the following:

Samples for testing may be requested by the Contract Administrator to ensure that the mix conforms to the MTO Lab Test No. LS 621.

330.10 BASIS OF PAYMENT**330.10.01 In-Place Full Depth Reclamation of Bituminous Pavement and Underlying Granular - Item**

Subsection 330.10.01 of OPSS 330 is amended by the addition of the following:

Payment for granular base will be made under the appropriate roadway granular item.

The depths of pavement to be processed which are shown in the contract documents shall be deemed to be incorrect for the purposes of paragraph (03) of clause GC 3.10.01 Changes in the Work of the MTO General Conditions of Contract, only when the average depth of all processing under the contract derived there from differs by more than 15 mm from the equivalent average depth derived from measurements taken by the Contract Administrator during the processing operation.

WARRANT: Always with this tender item.